



DIGITAL CLAMP MULTIMETER

1000A AC/DC Model: DCM 5410TR

- 3 5/6 Digits (6000 Counts)
- True RMS, Auto Ranging
- 60/600/1000A AC/DC
- Data Hold, B/L & Torch
- Continuity & Diode Test
- A.P.O., NCV & Live Wire Test
- Low Imp. ACV Meas. (TRMS)



Technical Specifications

Function	Range	Basic Accuracy
DC Voltage	600mV, 6V, 60V, 600V, 1000V	±(0.5% reading + 7 digits)
AC Voltage (True RMS)	6V, 60V, 600V, 750V	±(1% rdg. + 10 digits)
DC Current	60A / 600A / 1000A	±(4% rdg. + 10 digits)
AC Current (True RMS)	60A / 600A / 1000A	±(4% rdg. + 10 digits)
Capacitance	1nF / 10nF / 100nF / 1µF / 10µF / 100µF /	±(5.0% + 10 digits)
Frequency	10Hz – 10MHz	0.3% + 3 digits
Temperature	-20°C to 1000°C / -4°F to 1832°F	—
Low Impedance ACV Measurement	6V, 60V, 300V	±(1% rdg. + 10 digits)
Resistance	600Ω, 6KΩ, 60KΩ, 600KΩ, 6MΩ,	±(1% rdg. + 5 digits)



Additional Details

Item	Details
Input Impedance	$\leq 3K\Omega$
Accessories Supplied	Test Leads, Carrying Pouch, User Manual, 2xAAA 1.5V
Dimensions	230 × 75 × 40 mm
Weight	Approx. 315g (Including Battery)

Other Facilities / Functions

- Functions
- NCV Test
- Live Wire Test
- Diode Test
- Continuity Test
- Duty Cycle
- Back Light
- Torch
- Auto Power Off
- Low Battery Indication
- Data Hold
- Min./Max.

Accessories Supplied

- Test Leads
- Carrying Pouch
- User Manual
- Battery – 2xAAA 1.5V (Installed / Kept aside)

Dimension & Weight

- 230 × 75 × 40mm
- Approx. 315gms (Including Battery)

