



# DIGITAL CLAMP MULTIMETER

DCM 2250 TR - True RMS

## 6000 Counts, Auto Ranging

- Features
- 6/60/600/1000A AC
- Data Hold
- MIN/MAX
- Back Light
- Torch
- Auto Power Off (A.P.O.)
- NCV & Live Wire Test
- Continuity Test
- Diode Test
- Low Impedance ACV Measurement (TRMS)



## Technical Specifications

Function	Range	Basic Accuracy
<b>DC Voltage</b>	600mV, 6V, 60V, 600V, 1000V	$\pm(0.5\%$ reading + 7 digits)
<b>AC Voltage (True RMS)</b>	6V, 60V, 600V, 750V	$\pm(1\%$ rdg. + 10 digits)
<b>AC Current (True RMS)</b>	6A / 60A / 600A / 1000A	$\pm(4\%$ rdg. + 10 digits)
<b>Low Impedance ACV Measurement</b>	6V, 60V, 300V	$\pm(1\%$ rdg. + 10 digits)
<b>Resistance</b>	600 $\Omega$ , 6K $\Omega$ , 60K $\Omega$ , 600K $\Omega$ , 6M $\Omega$ ,	$\pm(1\%$ rdg. + 5 digits)



## Additional Details

Item	Details
<b>Input Impedance</b>	$\leq 3K\Omega$
<b>Accessories Supplied</b>	Test Leads, Carrying Pouch, User Manual, Battery – 2x AAA
<b>Dimensions</b>	230 × 75 × 40 mm
<b>Weight</b>	Approx. 315g (Including Battery)

### Special Features / Facilities

- Functions
- NCV Test
- Live Wire Test
- Diode Test
- Continuity Test
- Back Light
- Torch
- Auto Power Off
- Low Battery Indication
- Data Hold
- Min./Max.

### Accessories Supplied

- Test Leads
- Carrying Pouch
- User Manual
- Battery – 2xAAA 1.5V (Installed / Kept aside)

### Dimension & Weight

- 230 × 75 × 40mm
- Approx. 315gms (Including Battery)

