

## Features

- 3 1/2 Digits (2000 Counts)
- Manual Ranging
- True RMS
- Built-In Stand & Holster
- Auto Ranging Capacitance Test
- Continuity (A/V), Diode & Tr. (hFE) Test
- A.P.O., NCV, D/H, REL Tests
- Backlight & Torch
- AC 750V Range Freq., Measurement
- Heavy Duty



### SPECIFICATIONS

SPECIFICATIONS		
DC Voltage	Range	200 mV, 2 V, 20 V, 200 V, 1000 V
	Basic Accuracy	± (0.5% rdg + 3 digits)
AC Voltage (True RMS)	Range	2 V, 20 V, 200 V, 750 V (AC Mains Freq. Test in 750V Range)
	Basic Accuracy	± (0.8% rdg + 5 digits) 40 Hz ~ 1 KHz Freq., Response.
DC Current	Range	200 μA, 2 mA, 20 mA, 200 mA, 20 A
	Basic Accuracy	± (0.8% rdg + 10 digits)
AC Current (True RMS)	Range	20 mA, 200 mA, 20 A
	Basic Accuracy	± (1.0% rdg + 15 digits) 40 Hz ~ 400 Hz Freq., Response.
Resistance	Range	200 Ω, 2 K Ω, 20 K Ω, 200 K Ω, 2 M Ω, 20 M Ω
	Basic Accuracy	± (0.8% rdg + 3 digits)
Capacitance	Range	6 nF ~ 20 mF (In 8 Ranges - Auto Ranging)
	Accuracy	± (3.5% rdg + 20 digits)
Other Facilities / Features	NCV, Torch, ACV Freq., Measurement, A/V Continuity Test, Diode Test, Tr. (hFE) Test, LCD Back Light, Data Hold, REL Measurement, Auto Power Off, Low Battery Indication.	
Accessories Supplied	Holster (Installed), Test Leads, User Manual & Battery - 2 x AA (Installed / Kept Aside)	
Dimension & Weight	178 x 86 x 52 mm & Approx. 360 gms. (With Batt. & Holster).	

\* All Specifications & appearances are subject to change without prior notice

